

Data sheet

Warning tape

Composition: PE-LD
Colour: Neutral
Processing: Extrusion
Additive: Red, Orange, yellow, blue, green or violet 3-6%

24. februar 2020

Side 1 af 1

Typical properties

Testing	Testing standard	Test condition	Value	Unit
Density	DIN EN ISO 1183	23°C	0,922	g/cm ³
Tensile strength	DIN EN ISO 527	1mm/min	26 (MD) 23 (TD)	MPa
Tensile elongation	DIN EN ISO 527	1mm/min	300% (MD) 500% (TD)	MPa

LETBEK A/S

Hornevej 18
6862 Tistrup
Denmark

CVR: DK-24257134

+45 7529 9444
info@letbek.com

letbek.com

Specifications

Purpose of use	Warning tape for cable protection
DIM wideness dimension	20-125mm
DIM thickness dimension	0,1-0,3mm
DIM length dimension	250-500m
Recycling rate	100%

LETBEK sp z o.o.

Ul. Poznańska 165
62-052 Komorniki
Poland

VAT: PL-7792494776

+48 601 841 919
infopl@letbek.com

letbek.com

Note:

The data listed in this document are based on our current state of knowledge. Specific specifications cannot be guaranteed nor can the suitability for specific applications be deduced from above data. The client is committed to convince himself of the suitability of the product. The data do not release the client from the obligation to sustain a qualified receipt control. Storage temperature of 25°C maximum product keeps stable for at least 24 months.

LETBEK A/S
31-03-2016, Denmark, Product Management.

